

PERFORMANCE SPECIFICATIONS (APERTURE 4.5M)

★ R. F SPECIFICATIONS	★ C-Band RECEIVE TRANSMIT		★ Ku-Band RECEIVE TRANSMIT	
1. Frequency	3.625-4.2GHz *3.4-4.2GHz	5.850-6.425GHz 5.925-6.725GHz	12.25 -12.75GHz *10.95-12.75GHz	14.0-14.5GHz
2. Gain at Midband	43.6dB	47.3dB	53.63dB	54.7dB
3. VSWR	1.25:1	1.25:1	1.25:1	1.25:1
4. Beamwidth (-3dB)	1.09°	0.71°	0.35°	0.3°
5. Antenna Noise Temperature				
5° Elevation	40 °K		71°K	
10° Elevation	29 °K		55°K	
20° Elevation	23 °K		47°K	
30° Elevation	19 °K		45°K	
6. Typical G/T at 20° Elevation, Clear Horizon, 4Ghz with 55°K LNA	24.8dB/ °K		32 dB/ °K (11.85Ghz, with 90°K LNA)	
7. Power Handling Capability		5kW		2kW
8. Feed Interface	CPR-229F	CPR-137G	WR-75F	WR-75G
9. Feed Insertion Loss	0.15dB	0.17dB	0.25dB	0.4dB
10. Cross Polarization Isolation				
On Axis	35dB	35dB	35dB	35dB
Within 1 dB Beamwidth	30dB	30dB	30dB	30dB
11. Port to Port Isolation (Tx-Rx with Filter)	≥85dB		≥85dB	
12. Axial Ratio (Circular Polarization) 2 Port Tx/Rx	1.3	1.09		
13. Sidelobes				
1st sidelobe		-14dB		-14dB
100λ/D° ≤ θ ≤ 48°		29—25Log θ dBi		29—25Log θ dBi
* Provided according to User's requirement				
★ MECHANICAL SPECIFICATION		★ ENVIRONMENTAL SPECIFICATIONS		
1. Azimuth Travel	360° continuous	1. Operational Wind Speed	35m/s	
2. Azimuth Travel Rate	0.5 °/s	2. Survival Wind Speed	55m/s	
3. Elevation Travel	5°-90° continuous	3. Ambient Temperature	-50°- 60°	
4. Elevation Travel Rate	0.5 °/s	4. Rain (operational and survival)	10cm/h	
5. Polarization Travel	±90 °	5. Solar Radiation	1000kcal/hm ²	
6. Materials above the hub	aluminum, steel and stainless steel	6. Relative Humidity	0%-100%	
7. Finish of Reflectors	white paint	7. Radial Ice	2.5cm	
8. Finish of Steel parts	hot dipped zinc	8. Seismic(Survival)	0.3G's Horizontal 0.1G's Vertical	
9. Weight (Gross / Net)	921kg/610kg			
10. Shipping Volume	6.1m ³			
	one of 20' container can including 4 units			

Design and specifications subject to change without notice

SUMAN SATELLITE TECHNOLOGY COMPANY

#17 Lan Dian Chang Road, HaiDian District, Beijing, China 100097

Tel: +86-10-88455265 Fax: +86-10-88454630 E-mail: sumant@public.bta.net.cn Website: www.sumante.com